Thermal Test



Midway Middle School Midway, Tennessee

Thermal Test

Earth Energy Engineering

Ewbank and Associates P.O. Box 148 Fairview, Oklahoma 73737 580-227-3352



P.O. Box 148, Fairview, Oklahoma 73737 Phone/Fax 580-227-3352 E-mail ewbank@fairview-ok.net

Thermal Conductivity Test Results Midway Middle School Midway, Tennessee

Earth Energy Engineering performed a thermal conductivity test at the Midway Middle School in Midway, Tennessee on September 6, 2001. Testing was done by Fred Allison with a Ewbank portable test unit.

The test borehole was 300 feet in depth and 4" in diameter. A 1" inch loop was installed and the borehole was backfilled with #8 stone. Static water level was reported. The formations encountered were reported as primarily limestone and shale.

The thermal conductivity (k) value for this borehole is 1.5 btu/degree F-hr-foot. This is an average conductivity per foot for the borehole. This value represents the rate at which the borehole and rock will transfer heat.

To accurately measure the thermal conductivity of the formation a borehole should be drilled and grouted with a bentonite grout to prevent any flow of water through the borehole.

All test equipment, methods, procedures, calculations, and interpretation is done in accordance with the recommendations and guidelines of the International Ground Source Heat Pump Association.

EARTH ENERGY/DENVER DIGGIN TEST HOLE DRILL LOG

DATE: Aug ID, 2001	DRILLER: Kewin Schischikowsky
1 1 1 0	TOTAL DEPTH : 100' 1
START DATE: 8/9	COMPLETION DATE: 8/10

HOLE#	DEPTH	CASING	FORMATIONS
1	Ø-5'	NONE	Red Clay
	5'-30'		Littled Cock
	30'-70'		Shale - Water @ 70'-8 GPM
	70'-300'		Hard Dark Shale
2	0-45'	NONE	Red Clay, Broken Rock
	45'-90'		Shale - Water (0 80' - 86PM
	90'-300'		Hard, Dark Shale
_3	0-50'	NONE	Red Clay, Broken Kock
	50'-98'		Shale - 2' VOID @ 98'
	98'-100'		2' VOID - Mud Seam
	<u> </u>		
		<u>_</u>	
			
			
1	1	ł	

BY: K- Church Should
DENVER DIGGIN SERVICES, INC.

APPROVED:	

EARTH ENERGY ENGINEERING, INC.